

牌号
Grade PWA1483&DD483



规格参数:
Specification:

直径: Diameter:	ø50-ø100	mm	公差: Tolerance:	±3	mm
长度: Length:	160-1500	mm	公差: Tolerance:	±10	mm
状态: State:	磨光 Grinding	车光 Lathing			

根据客户要求定制规格：长度，尺寸，公差和粗糙度等。
Customized specifications according to customers' requirements: length, dimensions, tolerances, roughness, etc.

化学成分:	国标	航标
Chemical composition:	National standard	Aviation standard

元素符号	成分%	元素符号	成分%
Element symbol	Composition%	Element symbol	Composition%
铬 <u>Cr</u>	11.6-12.7	钴 <u>Co</u>	8.5-9.5
铝 <u>Al</u>	3.4-3.8	钨 <u>W</u>	3.5-4.1
钼 <u>Mo</u>	1.65-2.15	锰 <u>Mn</u>	≤0.1
钽 <u>Ta</u>	4.8-5.2	磷 <u>P</u>	≤0.0025
硅 <u>Si</u>	≤0.05	硫 <u>S</u>	≤0.0012
碳 <u>C</u>	0.05-0.09	氧 <u>O</u>	10ppm
钛 Ti	3.9-4.25	氮 <u>N</u>	10ppm
镍 Ni	余量/Balance		